

## 2 Hour Fire Protection

Leave approx. 1½" for dial & handles.

### Features:

Massive 2" thick door, 5-1/4" overall • Active 1-1/4" chromed locking bolts  
Tempered glass relocker • Chrome plated die-cast handle  
Adjustable shelves • Stainless facia plates



Group II Lock  
& G Lock

### Construction:

All around the world, the Mutal Gem Vault sets the standard in TL-15 and TL-15x6 protection. The Gem Vault's body consists of 9,000 PSI concrete embodied with corundum aggregate and encased in a double layer of high-tensile steel. The door is nearly 5-1/4" in overall thickness which includes 2" of solid barrier material. The Gem Vaults TL 15x6 body consists of 12,000 PSI concrete embodied with similar ingredients to the above but offers complete 6x sided protection.

### Protection:

Massive 1-1/4" chromed locking bolts, secured with a high security U.L. Listed Group II combination lock are standard on the Gem Vault. The lock is mounted on a magnesium anti-drilling and cutting plate, and as an extra measure, a plate of tempered glass connected to a randomly placed relocker is mounted behind the combination lock.

### GV-1412

Outside: 20" X 18.5" X 20.5" • Inside: 14" X 12.5" X 12"  
Weight: 480 lbs. cu.ft.:1.2 shelf: 1

### GV-1912

Outside: 25" X 20.5" X 20.5" • Inside: 19" X 18.5" X 18"  
Weight: 560 lbs. cu.ft.:1.6 shelf: 1

### GV-1918

Outside: 25" X 24.5" X 27.5" • Inside: 19" X 18.5" X 18"  
Weight: 850 lbs. cu.ft.:3.6 shelf: 1

### GV-2512

Outside: 31" X 18.¼" X 20.½" • Inside: 25" X 12.½" X 12"  
Weight: 650 lbs. cu.ft.:2.2 shelf: 1

### GV-2520

Outside: 31" X 26¼" X 29" • Inside: 25" X 20" X 21"  
Weight: 1000 lbs. cu.ft.:6.2 shelf: 2

### GV-3020

Outside: 36" X 26¼" X 29" • Inside: 29" X 20" X 21"  
Weight: 1150 lbs. cu.ft.:7.3 shelf: 2

### GV-4520

Outside: 51" X 26.5" X 29" • Inside: 45" X 20.5" X 21"  
Weight: 1600 lbs. cu.ft.:11.2 shelf: 3

### GV-5920

Outside: 65" X 26.5" X 29" • Inside: 59" X 20.5" X 21"  
Weight: 1750 lbs. cu.ft.:14.7 shelf: 3

## MUTALSAFES



UL-TL15 Gem Vault

**CLASS 2 UL-TL15**